

## FLEXIBLE SIGNAL / MICROPHONE



### Application

Flexible Signal / Microphone Cables are used for the interconnection of microphones, audio equipment, electrical equipment and instruments

### Construction

- Stranded Tinned Copper conductor
- Modified PVC Insulation
- Colour coded cores
- Tinned Copper wire braid giving 87% + coverage
- Flame-retardant PVC outer sheath - Black

### Packing

- 100, 200, 300, 400, 500mt/drum or as required.

Part Number	No. of Core	Number of Cores/DIA (mm)	Nominal Area/Core (mm)	Nominal O.D. (mm)
SIG162002SC	2	16/0.20	0.5	5.5
SIG162003SC	3	16/0.20	0.5	5.6
SIG162004SC	4	16/0.20	0.5	6
SIG162006SC	6	16/0.20	0.5	7.2
SIG162010SC	10	16/0.20	0.5	8.9
SIG162012SC	12	16/0.20	0.5	9.0
SIG162018SC	18	16/0.20	0.5	10.7
SIG162025SC	25	16/0.20	0.5	12.6

COLOUR CHART FOR SIGNAL CABLE							
Core No.	Colour	Core No.	Colour	Core No.	Colour	Core No.	Colour
1	Red	8	Violet	15	Yellow/Red	22	Orange/Blue
2	Blue	9	Orange	16	White/Red	23	Green/Blue
3	Green	10	Pink	17	Red/Black	24	Grey/Blue
4	Yellow	11	Turquoise	18	Red/Brown	25	Yellow/Green
5	White	12	Grey	19	Yellow/Blue		
6	Black	13	Red/Blue	20	White/Blue		
7	Brown	14	Red/Green	21	Blue/Black		